

ENGINEERING & MANAGEMENT EXAMINATIONS, JUNE - 2009 ELECTRICAL MACHINES - I SEMESTER - 4

		1.0		The state of the s	
Time:	3 Hours	1			[Full Marks: 70

		(Multiple	Choice Type Questions)	
. Cho	ose th	e correct alternatives for	any ten of the following:	10 × 1 = 10
i)	The	number of parallel path	s in a 8-pole D.C. machine, wave we	ound is
	a)	8	b) 4	
	c)	2	d) none of these.	
11)		.C. series motor is never	switched on without load connecte	ed at rated voltage
	a)	the field current initial	lly zero	
	b)	the motor does not acc	celerated	
Same Same Albana Sama	c)	the speed becomes da	ngerously high	
<u>~</u>	d)	none of these.		
iii)	Trai	nsformer core are made	up of laminated sheet to reduce	
	a)	hysteresis loss		
	b)	eddy current loss		
	c)	copper loss		
	d)	none of these		
	e)	all of these.		



	a)	1000 rpm	b)	1500 rpm
	c)	750 rpm	d)	800 rpm.
v)	Absc	ence of odd harmonics in	magneti	sing current in a 3-phase core
	tran	sformer will make the voltage	wave	
	a)	sinusoidal	b)	non-sinusoidal
	c)	asymmetrical	d)	none of these.
vi)	A 1	l transformer is used as		
	a)	pulse transformer	b)	isolating transformer
	c)	potential transformer	d)	current transformer.
vii)	Tert	lary winding is used in case o	f	
	a)	delta-delta	b)	star-zigzag
	c)	star-star	d)	none of these.
viii)	The	direction of rotation of a D.C	. shunt	motor can be reversed by interchar
	the			
	a)	supply terminals only		
	b)	field terminals only		
	c)	armature terminals only		
	d)	both field and armature term	ninals.	
ix)		ound rotor induction motor	can be	e distinguished from a squirrel
	a)	size of the frame	b)	direction of rotation
	c)	diameter of the shaft	d)	presence of slip ring.



X)	A D.C. snunt generator when driven without any excitation shows an open circuit							
	voltage of 10 volts. When the field winding is excited, the voltage dropped to zero							
	The reason is							
	a)	there is not residual magnetism						
	b)	field resistance is greater than the critical resistance						
	c)	field winding is wrongly connected						
4 4 7	d)	none of these.						
xi)	For	a slip ring induction motor, if the rotor resistance is increased, then						
	a)	starting torque and efficiency increases						
	b)	starting torque and efficiency decreases						
•	c)	starting torque decreases but efficiency increases						

GROUP - B

(Short Answer Type Questions)

Answer any three of the following questions.

 $3 \times 5 = 15$

- 2. Show how there is saving in conductor material in an auto-transformer compared to a two winding transformer having same kVA rating.
- 3. Determine the steps of the resistance for a shunt motor starter using resistance control method.
- 4. Derive the expression for developed torque in a 3-phase induction motor and state the conditions for maximum torque.
- 5. What is armature reaction? Describe the effects of armature reaction on the operation of a D.C. machine. How is the armature reaction minimised? 1 + 2 + 2

4646 (16/06)



- 6. Explain the tests to be conducted on three isolated secondary windings of a 3-phase transformer for connecting them
 - i) in star
 - ii) in delta.

3 + 2

GROUP - C

(Long Answer Type Questions)

Answer any three of the following questions.

 $3 \times 15 = 45$

- 7. a) What is the advantage of V-V connection of transformer?
 - b) Three single-phase transformers are connected in delta. If one of the transformers is found faulty and removed, what will be the reduction in kVA supplied?
 - Three single-phase transformers, connected in Δ/Δ supply a balanced 3-phase load of 1500 kW at 4400 V at 0.8 power factor lagging. The transformers are supplied from 3-phase mains at 11000 V. Find the current in the windings of each transformer. If one of the transformers is found faulty and is removed and the supply is maintained in V-V connection, determine the currents in the windings and the power supplied by each of the transformers. 2 + 5 + (2 + 2 + 4)
- 8. a) What are different phasor groups? Why are phasor groups mentioned in the name plate of a transformer?
 - b) Draw the phasor and connection diagrams of transformers connected
 - 1) Yd 11
 - ii) Dz 6
 - iii) Dy 11
 - iv) Dd 6.

(2+1)+12



- 9. a) Describe the different types of excitation of D.C. machines. Explain the build up process of voltage of a D.C. shunt generator. Mention the different reasons of failure to building up process of D.C. shunt generator.
 - b) A 10 kW, 250 V shunt generator having an armature resistance of 0·1 Ω and field resistance of 250 Ω delivers full load at rated speed of 800 rpm and at rated voltage of 250 volt. Machine now runs as motor while taking 10 kW at 250 volt. Find the speed of the machine as motor. Neglect brush contact drop.
- 10. a) Bring out the difference between an autotransformer and induction regulator.
 - b) Explain with circuit diagram the principle of operation of a single-phase induction regulator.
 - c) Draw the circuit diagram of a 3-phase induction regulator and explain.
 - d) Why is compensating winding necessary for single phase induction regulator but not necessary for 3-phase? 2+6+3+4
- 11. Write short notes on any three of the following:

 3×5

- a) On-load tap changer of a transformer
- b) Three-phase to two-phase conversion
- c) Cogging and Crawling in induction motors
- d) Determination of external characteristics of separately excited D.C. generator from its open circuit characteristics.
- e) Different methods of starting of induction motors.

END