2 Ecsimins) comb/ widle of & 9/3/451 commy/ vecod

on. 5597-09.

## (REVISED COURSE)

SP-7799

(3 Hours)

[Total Marks: 100

N.B		(2)	Attempt any four questions of remaining six questions.  Figures to the right indicate full marks for the question.  Assume suitable data if required.	
1.	<ul> <li>(a) Explain Noise Factor of Amplifier in Cascade.</li> <li>(b) Compare F.M. and A.M. system.</li> <li>(c) Explain Shannon's Theorem for channel capacity.</li> <li>(d) Explain Matched Filter.</li> </ul>		5 5 5	
2.	(a) (b)	(ii)	Distortions in the envelope detector.  Effect of Noise in F.M. system.	5 5 5
3.	(a) (b)	Explain pulse width modulation and demodulation.  What is need of multiplexing, explain FDM in detail.		10 10
4.	(a) (b)	Explain delta-modulation and adaptive delta-modulation. Band limited 4 kHz signal are sampled at the Nyquist rate and quantized into 4 levels $Q_1$ , $Q_2$ , $Q_3$ and $Q_4$ with probability. $P_1 = P_2 = 1/18$ and $P_3 = P_4 = 3/8$ . Find rate of information.		10
5.	(a) (b)	WI	nat is effect of Gaussian Noise on Digital Communication. plain inter symbol interference and flow it reduce.	10 10
6.	(a) (b)	and the proof of the section and the section of the		10 10
7.	W	rite s (a) (b) (c) (d)	Cyclic Codes Noise Triangle QAM Thermal Noise.	20