

DO NOT OPEN THE POLYTHENE BAG/SEAL OF THE BOOKLET UNTIL YOU ARE TOLD TO DO SO

Booklet Serial No.

1010019

JA 2015  
PAPER I  
प्रश्नपत्र I

Civil and Structural  
सिविल एवं संरचनात्मक

Time Allowed : 2 Hours

निर्धारित समय : 2 घंटे

Maximum Marks : 200

अधिकतम अंक : 200

Read the following instructions carefully before you begin to answer the questions.

This Booklet contains questions in English as well as in Hindi.

प्रश्नों के उत्तर देने से पहले नीचे लिखे अनुदेशों को ध्यान से पढ़ लें। इस पुस्तिका में प्रश्न अंग्रेजी तथा हिन्दी दोनों में दिये गये हैं।

#### INSTRUCTIONS TO CANDIDATES

- This Booklet contains 200 questions in all comprising the following three tests:  
Test I : General Intelligence & Reasoning (50 Questions)  
Test II : General Awareness (50 Questions)  
Test III : General Engineering (Civil and Structural) (100 Questions)
- In questions set bilingually in English and Hindi, in case of discrepancy, the English version will prevail.
- All questions are compulsory and carry equal marks.
- The paper carries negative marking. 0.25 marks will be deducted for each wrong answer.
- Before you start to answer the questions you must check up this Booklet and ensure that it contains all the pages (1-32) and see that no page is missing or repeated. If you find any defect in this Booklet, you must get it replaced immediately.
- You will be supplied the Answer Sheet separately by the Invigilator. Before you actually start answering the questions, you must complete and code the details of Name, Roll Number, Ticket Number, Booklet Serial No. and Stream i.e. Civil and Structural OR Electrical OR Mechanical etc. in the Answer Sheet carefully. You must also put your signatures and Left-Hand thumb impression on the Answer Sheet at the prescribed place before you start answering the questions. These instructions must be fully complied with, failing which, your Answer Sheet will not be evaluated and you will be awarded 'ZERO' mark.
- Answers must be shown by completely blackening the corresponding circle on Side-II of the Answer Sheet against the relevant question number by Black/Blue Ball-point Pen only. Answers which are not shown by Black/Blue Ball-point Pen will not be awarded any mark.
- A machine will read the coded information in the OMR Answer Sheet. In case the information is incomplete or different from the information given in the application form, such candidate will be awarded 'ZERO' mark.
- The Answer Sheet must be handed over to the Invigilator before you leave the Examination-Hall.
- Failure to comply with any of the above instructions will render a candidate liable to such action/penalty as may be deemed fit.
- The manner in which the different questions are to be answered has been explained at the back of this Booklet (Page No. 32), which you should read carefully before actually answering the questions.
- Answer the questions as quickly and as carefully as you can. Some questions may be difficult and others easy. Do not spend too much time on any question.
- No rough work is to be done on the Answer Sheet. Space for rough work has been provided below the questions.
- "Mobile phones and wireless communication devices are completely banned in the examination halls/rooms. Candidates are advised not to keep mobile phones/any other wireless communication devices with them even switching it off, in their own interest. Failing to comply with this provision will be considered as using unfair means in the examination and action will be taken against them including cancellation of their candidature."

#### उम्मीदवारों के लिए अनुदेश

- इस पुस्तिका में कुल 200 प्रश्न हैं, जिनमें निम्नलिखित तीन परीक्षण शामिल हैं :  
परीक्षण I : सामान्य बुद्धि और तर्क (50 प्रश्न)  
परीक्षण II : सामान्य जानकारी (50 प्रश्न)  
परीक्षण III : सामान्य इंजीनियरी (सिविल एवं संरचनात्मक) (100 प्रश्न)
- अंग्रेजी और हिन्दी भाषा में तैयार किए गए द्विभाषी प्रश्नों में कोई विसंगति होने की स्थिति में अंग्रेजी विवरण मान्य होगा।
- सभी प्रश्न अनिवार्य हैं तथा सबके बराबर अंक हैं।
- प्रश्न पत्र में नकारात्मक अंकन होगा। हर गलत उत्तर के लिए 0.25 अंक काटा जाएगा।
- प्रश्नों के उत्तर देने से पहले आप इस पुस्तिका की जांच करके देख लें कि इसमें पूरे पृष्ठ (1-32) हैं तथा कोई पृष्ठ कम या दुबारा तो नहीं आ गया है। यदि आप इस पुस्तिका में कोई त्रुटि पाएं, तो तत्काल इसके बदले दूसरी पुस्तिका से लें।
- निरीक्षक द्वारा आपको उत्तर-पत्रिका अलग से दी जाएगी। प्रश्नों के उत्तर वास्तव में शुरू करने से पहले आप उत्तर-पत्रिका के नियमावली के अनुसार अपना नाम, रोल नम्बर, टिकट नम्बर, पुस्तिका क्रम संख्या तथा विषय अर्थात् सिविल एवं संरचनात्मक या विद्युत या यांत्रिक आदि अवश्य लिखें। प्रश्नों के उत्तर देने से पहले उत्तर-पत्रिका पर निर्धारित स्थान में आप अपने हस्ताक्षर एवं बाएं हाथ के अंगूठे का निशान भी अवश्य लगाएं। उपर्युक्त अनुदेशों का पूरी तरह अनुपालन किया जाए, अन्यथा आपकी उत्तर-पत्रिका को जांचा नहीं जायेगा और 'शून्य' अंक दिया जाएगा।
- उत्तर-पत्रिका में सभी उत्तर Side-II में प्रश्न संख्या के सामने दिये गये सम्बन्धित गोलाकार खानों को केवल काला/नीला बॉल-पॉइंट पेन से पूरी तरह काला करके दिखाएँ। जो गोलाकार खाने काला/नीला बॉल-पॉइंट पेन से नहीं भरे जाएँ, उनके लिए कोई अंक नहीं दिया जाएगा।
- ओ.एम.आर. उत्तर-पत्रिका में भरी गई कूट सूचना को एक मशीन पढ़ेगी। यदि सूचना अपूर्ण है अथवा आवेदन प्रपत्र में दी गई सूचना से भिन्न है, तो ऐसे अभ्यर्थी को 'शून्य' अंक दिया जाएगा।
- परीक्षा-भवन छोड़ने से पहले परीक्षार्थी को उत्तर-पत्रिका निरीक्षक के हवाले कर देनी चाहिए।
- ऊपर के अनुदेशों में से किसी एक का भी पालन न करने पर उम्मीदवार पर बिबेकानुसार कार्यवाही की जा सकती है या वण्ड दिया जा सकता है।
- विभिन्न प्रश्नों के उत्तर देने की विधि इस पुस्तिका के पीछे (पृष्ठ संख्या 32) में छपे हुए निर्देशों में दे दी गई है, इसे आप प्रश्नों के उत्तर देने से पहले ध्यानपूर्वक पढ़ लें।
- प्रश्नों के उत्तर जितनी जल्दी हो सके तथा ध्यानपूर्वक दें। कुछ प्रश्न आसान तथा कुछ कठिन हैं। किसी एक प्रश्न पर बहुत अधिक समय न लगाएं।
- कोई रफ कार्य उत्तर-पत्रिका पर नहीं करना है। रफ कार्य के लिए स्थान प्रश्नों के नीचे दिया गया है।
- "परीक्षा हॉलों/कमरों में मोबाइल फोन तथा बेतार संचार साधन पूरी तरह निषिद्ध हैं। उम्मीदवारों को उनके अपने हित में सलाह दी जाती है कि मोबाइल फोन/किसी अन्य बेतार संचार साधन को स्विच ऑफ करके भी अपने पास न रखें। इस प्रावधान का अनुपालन न करने पर परीक्षा में अनुचित उपकरणों का प्रयोग माना जाएगा और उनके विरुद्ध कार्रवाई की जाएगी, उनकी अभ्यर्थिता रद्द कर देने सहित।"

इस पुस्तिका की सील/पांतीथीन बैग तब तक न खोलें जब तक कहा न जाए

**TEST - III : GENERAL ENGINEERING (CIVIL & STRUCTURAL)**

101. The thickness of the flange of a tee beam of a ribbed slab is assumed as  
(A) half the thickness of the rib  
(B) thickness of the concrete topping  
● depth of the rib  
(D) width of the rib
102. Co-efficient of wind resistance of a circular surface is  
(A)  $\frac{2}{3}$  (B)  $\frac{3}{2}$  (C)  $\frac{1}{3}$  ●  $\frac{1}{2}$
103. Total number of elastic constants of an isotropic material are  
● 2 (B) 3 (C) 4 (D) 5
104. The stiffness of a spring is  
(A) load per coil of the spring  
● load required to produce unit deflection  
(C) load required to compress the spring up to shearing proportional limit  
(D) the load required for breaking the spring
105. Creep of a material is  
(A) not being ductile  
(B) to become brittle  
(C) disappearance of deformation on removal of load  
● continued deformation with time under sustained loading
106. A propped cantilever is indeterminate externally of  
(A) second degree (B) fourth degree  
● first degree (D) third degree
107. Which of the following is a relatively ductile material?  
(A) High carbon steel (B) Bronze  
● Mild steel (D) Cast iron
108. A beam is supported over three rollers lying in the same plane. The beam is stable for  
(A) loading with no component perpendicular to the direction of beam  
(B) only when no load except self weight acts  
● loading with no component in the direction of the beam  
(D) any general loading
109. The resistance of an aggregate to the effect of hydration of cement and weather is called  
(A) impact value  
● soundness  
(C) crushing strength  
(D) abrasion resistance
110. Under which conditions highest water cement ratio is used?  
● Heavy sections such as piers, foundations etc. exposed to alternate wetting and drying  
(B) Heavy sections such as piers foundations etc. protected against rain and frost  
(C) Hydraulic structure exposed to rain and snow  
(D) Light structural members exposed to alternate wetting and drying
111. Snowcem is  
● coloured cement  
(B) powdered lime  
(C) chalk powder  
(D) mixture of chalk powder and lime
112. In a singly reinforced beam, if the concrete is stressed to its allowable limit earlier than steel, the section is said to be  
(A) economical section  
● over reinforced section  
(C) balanced section  
(D) under reinforced section

SPACE FOR ROUGH WORK



## ZONE TECH

Best Institute For J.En.  
Tonk Phatak, Jaipur

9828747676, 9460538611

113. In order to determine the allowable stress in axial compression, Indian Standard Institution has adopted
- Rankine's formula
  - Secant formula
  - Euler's formula
  - Perry-Robertson formula
114. The sag tie in a truss is mainly used to reduce
- moment and deflection
  - tension
  - weight of the truss
  - compression
115. A simply supported beam carrying uniformly distributed load will be safe in deflection if the ratio of its span and depth is
- $\frac{l}{d} < 24$
- $< 24$
  - $> 19$
  - $< 19$
  - $> 24$
116. The actual thickness of a butt weld when compared with the thickness of the plate is
- less
  - more or less
  - more
  - equal
117. The fillet weld whose axis is parallel to the direction of the applied load is known as
- side fillet weld
  - end fillet weld
  - flat fillet weld
  - diagonal fillet weld
118. Tacking rivets in compression plates exposed to weather have a pitch not exceeding 200 mm or
- 8 times the thickness of outside plate
  - 16 times the thickness of outside plate
  - 24 times the thickness of outside plate
  - 32 times the thickness of outside plate
119. The depth of the section of an upper column is much smaller than the lower column
- bearing plates are provided with column splice
  - filler and bearing plates are provided with column splice
  - filler plates are provided with column splice
  - neither filler nor bearing plates are provided with column splice
120. Web crippling in beams generally occurs at the points where
- concentrated loads act
  - bending moment is maximum
  - shear force is maximum
  - deflection is maximum
121. The minimum thickness of the plates used in pressed steel tanks is
- 4 mm
  - 5 mm
  - 6 mm
  - 3 mm
122. A column splice is used to increase
- the strength of the column
  - the rigidity of the column
  - the cross-sectional area of the column
  - the length of the column
123. Percentage increase of carbon in steel, decreases its
- hardness
  - ductility
  - strength
  - brittleness

SPACE FOR ROUGH WORK

## ZONE TECH

Best Institute For J.En.  
Tonk Phatak, Jaipur

9828747676, 9460538611

124. The process of providing smooth face and regular face to stones is known as  
(A) quarrying (B) seasoning  
(C) pitching (D) dressing
125. The bulking of sand occurs due to  
(A) Air in voids  
(B) Moisture in voids  
(C) Surface tension  
(D) Capillary action
126. The compressive strength of common building bricks should not be less than  
(A) 3.5 N/mm<sup>2</sup> (B) 5.5 N/mm<sup>2</sup>  
(C) 7.5 N/mm<sup>2</sup> (D) 10.5 N/mm<sup>2</sup>
127. The natural bedding plane of stones and the direction of pressure in stone masonry is  
(A) normal (B) parallel  
(C) at 30° (D) at 45°
128. Following stone is suitable for damp-proofing  
(A) Slate (B) Marble  
(C) Laterite (D) Granite
129. The number of standard bricks in one cubic metre of brick masonry is  
(A) 300 (B) 500  
(C) 700 (D) 1000
130. The resistance of a material to penetration is  
(A) Toughness (B) Hardness  
(C) Fatigue (D) Roughness
131. The standard size of a masonry brick is  
(A) 18 cm × 8 cm × 8 cm  
(B) 18 cm × 9 cm × 9 cm  
(C) 19 cm × 9 cm × 9 cm  
(D) 19 cm × 8 cm × 8 cm
132. Cement should have least percentage of  
(A) Aluminium oxide  
(B) Iron oxide  
(C) Silica  
(D) Magnesium oxide
133. Turpentine oil is used in paint as a  
(A) Base (B) Carrier  
(C) Drier (D) Thinner
134. Connecting pipe in mm for septic tank should not be less than  
(A) 150 (B) 100 (C) 50 (D) 25
135. Total depreciation during first five years of a cement concrete structure is  
(A) zero per cent (B) 0.5 per cent  
(C) 1 per cent (D) 2 per cent
136. Estimate for electrical wiring is prepared on the basis of  
(A) Voltage  
(B) Power  
(C) Number of appliances  
(D) Number of points
137. Which of the following tax generally not applicable to residential building is  
(A) Municipal tax (B) Property tax  
(C) Sales tax (D) Wealth tax
138. The value of demolished material is known as  
(A) Scrap value (B) Salvage value  
(C) Resultant value (D) Material value

SPACE FOR ROUGH WORK

## ZONE TECH

Best Institute For J.En.

Tonk Phatak, Jaipur

9814767694 960538811

139. Slump test for concrete is carried out to determine  
(A) Strength (B) Durability  
 Workability (D) Water content
140. The leaching action in concrete is the example of  
(A) decomposition (B) creeping  
 crystallization (D) chemical reaction
141. Poission's ratio of cement concrete is about  
(A) 0.28 (B) 0.50  0.40 (D) 0.15
142. The span to depth ratio limit is specified in IS : 456-2000 for the reinforced concreted beams, in order to ensure that the  
(A) shear failure is avoided  
(B) tensile crack width is below a limit  
 deflection of the beam is below a limiting value  
 stress in the tension reinforcement is less than the allowable value
143. A  $300 \times 300$  mm R.C. column in reinforced with 8 bars, four bars are of 12 mm diameter. The diameter of lateral ties is 6 mm. The pitch of lateral ties shall be kept as  
 288 mm (B) 160 mm  
(C) 192 mm (D) 300 mm
144. The width of lacing bars in mm is kept  
 twice the nominal rivet diameter  
 thrice the nominal rivet diameter  
(C) maximum of the all rounded to nearest 5 mm  
(D) equal to normal rivet diameter
145. The bearing stress at bends for limit state method compared to working stress method of design is  
 1.5 times more (B) 2.5 times more  
(C) 2.5 times less (D) 1.5 times less
146. The base width of retaining wall of height  $h$  is generally taken as,  $b =$   
(A)  $0.8 h$  (B)  $0.95 h$   
  $0.6 h$  (D)  $0.3 h$
147. The steel beam of light section placed in plain cement concrete are called  
 filler joists (B) concrete joists  
(C) simple joists (D) joists
148. Partial safety factor on steel stresses is  
(A) 1.67  1.15 (C) 1.77 (D) 1.5
149. When a load is exerted or transferred from one surface to another in contact, the stress is known as  
 bearing stress (P, shear stress  
(C) binding stress (D) direct stress
150. When R.C.C. footing is not to extend in the plot of the neighbouring house, the type of footing preferred is  
(A) cellular flat not footing  
(B) inverted flat not footing  
 strap footing  
(D) both (A) and (B) above

SPACE FOR ROUGH WORK

300  
→  $16 \times 12$

$G = 0.2$

151. The construction joints in cement concrete
- (A) should not be provided at the corners
  - (B) should be spaced at a distance of 3 m apart in case of huge structures
  - (C) should be located where shear force is large
  - (D) should be located where bending moment is large
152. The fineness modulus of an aggregate is roughly proportional to
- (A) average size of particles in the aggregate
  - (B) grading of the aggregate
  - (C) specific gravity of the aggregate
  - (D) shape of the aggregate
153. The aggregate is said to be flaky when
- (A) its length is equal to 1.8 times its mean dimension
  - (B) its length is equal to its mean dimension
  - (C) its least dimension is equal to its mean dimension
  - (D) its least dimension is three fifth of its mean dimension
154. The soundness of cement is tested by
- (A) Vicat's apparatus
  - (B) Le Chatelier's apparatus
  - (C) Compression testing machine
  - (D) Standard briquette test
155. In lime concrete, lime is used as
- (A) admixture
  - (B) binding aggregate
  - (C) fine aggregate
  - (D) coarse aggregate
156. The minimum quantity of cement content needed in one m<sup>3</sup> of a reinforced concrete which is exposed to sea weather conditions is (in kg)
- (A) 350 (B) 200  (C) 250 (D) 300
157. Shrinkage in concrete increases its
- (A) bond strength
  - (B) compressive strength
  - (C) flexural strength
  - (D) tensile
158. The strength of concrete mainly depends on
- (A) quality of fine aggregates
  - (B) water cement ratio
  - (C) fineness of cement
  - (D) quality of coarse aggregates
159. Green concrete may be made by adding
- (A) iron hydroxide
  - (B) barium manganate
  - (C) iron oxide
  - (D) chromium oxide
160. Gypsum is added to cement in small quantity to
- (A) control initial setting time
  - (B) control final setting time
  - (C) give colour to the cement
  - (D) make cement hydrophobic
161. The Indian standard mix design for fly ash and cement concrete recommends water content
- (A) to increase by 3% to 5%
  - (B) to reduce by 15%
  - (C) to increase by 15%
  - (D) to reduce by 3% to 5%

SPACE FOR ROUGH WORK

**ZONE TECH**

Best Institute For J.En.  
Tonk Phatak, Jaipur

9828747676, 9460538611

162. One cubic metre of mild steel weighs about
- (A) 1000 kg (B) 3625 kg  
 7850 kg (D) 12560 kg
163. The total length of a cranked bar through a distance ( $d$ ) at  $45^\circ$  in case of a beam of effective length  $L$ , and depth ( $d$ ) is
- (A)  $L + 0.42 d$  (B)  $L + 2 \times 0.42 d$   
(C)  $L - 0.42 d$    $L - 2 \times 0.42 d$
164. For building project estimate which method is generally used in PWD ?
- (A) Long wall and short wall method  
 Centre line method  
(C) Crossing method  
(D) Short wall method
165. An estimate is
- (A) cost of the structure using thumb rules  
(B) random guess of cost of structure  
 probable cost arrived at before construction  
(D) actual cost of construction
166. The depth of foundation is usually calculated from
- Rankine's formula  
(B) Newton's formula  
(C) De Almbert's formula  
(D) Gutter's formula
167. When two points of surveying are mutually invisible the following method of ranging is adopted
- (A) Direct ranging  
 Indirect ranging  
(C) Horizontal ranging  
(D) Vertical ranging
168. The distance between two brass rings in a surveyor's chain is
- 20 cm (B) 40 cm  
(C) 75 cm (D) 1 m
169. The sum of the interior angles of a closed traverse is equal to
- $(2n - 4) 90^\circ$  (B)  $(3n - 4) 90^\circ$   
(C)  $(2n - 4) 180^\circ$  (D)  $(3n - 4) 180^\circ$
170. Survey line provided to verify the accuracy of the framework is known as
- (A) Tie line (B) Base line  
(C) Subsidiary line  Check line
171. The total number of links provided in a Gunter's chain is
- (A) 132  100 (C) 66 (D) 50
172. If the fore bearing of a line is observed to be  $AB 12^\circ 24'$ , the back bearing of line  $AB$  should be
- (A)  $102^\circ 24'$  (B)  $77^\circ 36'$   
(C)  $167^\circ 36'$    $192^\circ 24'$
173. The direction of a line relative to a given meridian is known as
- (A) Angle of line (B) Direction of line  
 Bearing of line (D) Relative meridian
174. When compared with chain surveying plane table is
- more accurate (B) less accurate  
(C) not accurate (D) accurate
175. Number of satellites involved in the orbit for the GPS survey technique
- (A) 14  24 (C) 34 (D) 44

**ZONE TECH**  
Best Institute For J.En.  
Tonk Phatak, Jaipur  
9828747676, 9460538611

**ZONE TECH**  
Best Institute For J.En.  
Tonk Phatak, Jaipur  
9828747676, 9460538611

SPACE FOR ROUGH WORK

$0 = FB \pm 180$

$180.60$   
 $12.24$

$179.60$

176. Harbour model are based on the following law  
 (A) Froude law       Reynold's law  
 (C) Stoke's law      (D) Euler's law
177. For stability of floating bodies, the metacentre should be  
 above the centre of gravity  
 (B) below the centre of gravity  
 (C) above the centre of buoyancy  
 (D) below the centre of buoyancy
178. A vessel containing water of depth  $h$  is accelerated upward with an acceleration of  $\frac{g}{2}$ . The pressure at the bottom of the vessel is  
 (A)  $\gamma h$     (B)  $\frac{\gamma h}{2}$     (C)  $2\gamma h$       $\frac{3}{2}\gamma h$
179. The most desirable alignment of an irrigation canal is along  
 the ridge line  
 (A) the contour line  
 (C) normal to contour line  
 (D) the valley line
180. Clay is an example of  
 (A) aquifer       aquitard  
 (C) aquifuge      (D) aquiclude
181. Aggregate impact value indicates which of the following properties of aggregates?  
 (A) Durability       Toughness  
 (C) Hardness      (D) Strength
182. The shape of the STOP sign according to IRC : 67-2001 is  
 (A) Circular      (B) Triangular  
 (C) Rectangular       (D) Octagonal
183. Pollution potential of domestic sewage generated in a town and its industrial sewage can be compared with reference to  
 (A) their BOD value  
 (B) population equivalent  
 (C) their volume  
 (D) the relative density
184. The valve which protects the water meter from the damages of water hammer  
 (A) pressure relief valve  
 (B) stop cock  
 (C) reflux valve  
 (D) water hammer valve
185. In Brinell Hardness test, the type of indenter used is  
 (A) hard steel ball    (B) diamond cone  
 (C) mild steel ball    (D) hard steel cone
186. The intensity of direct longitudinal stress in the cross-section at any point distant  $r$  from the neutral axis, is proportional to  
 (A)  $\frac{1}{r^2}$     (B)  $\frac{1}{r}$     (C)  $r$     (D)  $r^2$
187. A column is known as medium size if its slenderness ratio is between  
 (A) 160 and 180    (B) 20 and 32  
 (C) 32 and 120     (D) 120 and 160
188. An arch may be subjected to  
 (A) shear force and thrust  
 (B) bending moment and shear force  
 (C) shear and axial force  
 (D) bending moment and axial force

SPACE FOR ROUGH WORK



**ZONE TECH**

Best Institute For J.En.  
Tonk Phatak, Jaipur

9828747676, 9460538611

189. Mean sea level (MSL) adopted by Survey of India for reference, is located at  
(A) Kolkata (B) Mumbai  
 (C) Karachi (D) Delhi
190. Black cotton soil is not suitable for foundation because of its  
(A) low bearing capacity  
(B) cohesive particles  
 (C) swelling and shrinkage  
(D) black colour
191. Optimum moisture content is obtained from  
(A) triaxial test  
 (B) standard proctor test  
(C) consolidation test  
(D) hydrometer test
192. The effective size of particles of soil is denoted by  
 (A)  $D_{10}$  (B)  $D_{20}$   
(C)  $D_{30}$  (D)  $D_{60}$
193. When the plasticity index of a soil is zero, the soil is  
(A) Clay (B) Silt  
 (C) Sand (D) Silty sand
194. Francis turbine is  
 (A) a reaction turbine  
(B) an impulse turbine  
(C) a tangential flow impulse turbine  
(D) an axial flow turbine
195. Most economical circular channel gives maximum discharge while  
 (A) flow depth = 0.95 diameter  
(B) flow velocity high  
(C) area of flow is full  
(D) wetted perimeter is least
196. Two pipe systems are said to be equivalent when  
(A) they carry same discharge  
(B) they are satisfying Bernoulli's theorem  
 (C) both have same head loss and discharge values  
(D) they are of same length and having same head loss
197. The specific speed of a pump is defined as the speed of a unit of such a size that it discharges  
(A) unit discharge at unit power  
(B) unit work at unit head loss  
 (C) unit discharge at unit head  
(D) unit volume at unit time
198. The dimensions of Chezy's  $C$  is  
(A) non-dimensional (B)  $L/T$   
(C)  $LT$   (D)  $[L/T^2]^{1/2}$
199. The velocity distribution for turbulent flow through circular pipes is  
(A) uniform (B) linear  
(C) parabolic  (D) logarithmic
200. With increase in temperature the viscosity of air and water varies as  
 (A) viscosity of air increases and viscosity of water decreases  
(B) viscosity of air increases and viscosity of water increases  
(C) viscosity of air decreases and viscosity of water decreases  
(D) viscosity of air decreases and viscosity of water increases

SPACE FOR ROUGH WORK

F 168 91 T ↑ air water