| Seat No.: | Enrolment No. |
|-----------|---------------|
| | |

GUJARAT TECHNOLOGICAL UNIVERSITY

B.E. Sem - III (Civil) Examination December/January 2009-10

Subject code: 130605 Subject Name: Concrete Technology
Date: 29 / 12 / 2009 Time: 11.00 am – 1.30 pm

| Tot | tal | Ma | rks: | 70 |
|-----|-----|----|------|----|
| | | | | |

| T 4 | 4 • | |
|--------|-------|-----|
| Instru | ctini | 16. |
| mou a | CUUI | 15. |

- 1. Attempt all questions.
- 2. Make suitable assumptions wherever necessary.
- 3. Figures to the right indicate full marks.
- Q.1 (a) Justify the statement: "Strength of aggregate plays important role in quality and strength of concrete".
 - (b) Define workability of concrete, Which are the different methods of measuring it in the laboratory? Explain any one of them.
- Q.2 (a) Enlist the different Laboratory tests of cement. Explain any one of them in detail.
 - (b) Define Admixtures and Additives. Enlist the different admixtures used in concrete construction. Explain the function and property of any two types of admixtures

OR

- (b) Describe briefly the chemical composition, major compounds formed 07 and hydration of cement.
- Q.3 (a) Enlist the different types of cement. Discuss about the properties and applications for any two types of cement in concrete construction.
 - (b) How will you check the cement on field? How is the field testing 05 important?
 - (c) Explain the qualities of water required for production of concrete. 04

OR

- Q.3 (a) Which are the factors affecting strength of concrete? Explain any one 05 of them.
 - (b) Find the Fineness Modulus of aggregate for the following result of sieve analysis. What is its utility?

| I.S | 40 | 20 | 10 | 4.75 | 2.36 | 1.18 | 600 | 300 | 150 |
|---------|-----|----|----|------|------|------|-----|-----|-----|
| Sieve | | | | | | | | | |
| % | 100 | 70 | 50 | 40 | 20 | 2 | 0 | 0 | 0 |
| Passing | | | | | | | | | |

- (c) Explain the effect of size, shape, texture and grading of aggregate on outconcrete.
- Q.4 (a) Which are the different steps needed for process of manufacturing of concrete? Describe in detail the compaction of concrete.
 - **(b)** Describe in detail the segregation and bleeding

OR

- Q.4 (a) What is non destructive testing of Concrete? Discuss pulse velocity 07 method.
 - (b) Discuss various aspect of durability of concrete. What measures are taken by IS code to ensure durable structure?
- Q.5 (a) Write Short note on
 (i) Under water concrete (ii) Shotcrete
 - (i) Under water concrete (ii) Shotcrete
 (b) Explain effect of age of concrete on its strength. What will be the effect of size of specimen on concrete strength?

07

- Q.5 For the construction of road, concrete mix design is adopted. The road (a) is to be designed for the minimum compressive strength of 20 Mpa at
 - 28 days. The standard deviation of 3.5 Mpa is available during the laboratory testing of the mix. The specific gravity of C.A. is 2.85 and its dry rodded bulk density is 1600kg/m³. The maximum size of aggregate to be used is 40 mm. The specific gravity of fine aggregate is 2.6 and its fineness modulus is 2.75. A slump of 30 mm is specified. An OPC is used and it is required that note more than 2.5% test results allow to fall below specified strength. F.A. contains 5% surface moisture and C.A absorbs 3%. Work out the proportion of various ingredient material of Concrete after applying necessary correction for:
 - (i) 1 bag of cement
 - (ii) 1 m³ of Concrete

Table 1

| 1 doic 1 | | | | |
|-----------------|-------|--|--|--|
| % of result | Value | | | |
| allowed to fall | 'k' | | | |
| below min | | | | |
| | | | | |
| 1.0 | 2.33 | | | |
| 2.5 | 1.96 | | | |
| 6.6 | 1.50 | | | |
| 16.0 | 1.00 | | | |
| | | | | |

Table 2

| | aut 2 | |
|----------|-------|-----------|
| Avg. | Comp | Effective |
| strength | at 28 | W/c |
| days (MI | Pa) | Ratio(by |
| | | mass) |
| 45 | | 0.38 |
| 40 | | 0.43 |
| 35 | | 0.48 |
| 30 | | 0.55 |
| 25 | | 0.62 |
| 20 | | 0.70 |

Table:3

| 14016.5 | | | | | | |
|---------------|--|------|------|--|--|--|
| Water requ | Water requirement for maximum size of aggregate of | | | | | |
| Slump | 10mm | 20mm | 40mm | | | |
| 25 to 50 mm | 206 | 182 | 162 | | | |
| 75 to100 mm | 226 | 203 | 177 | | | |
| 150 to 175mm | 240 | 212 | 188 | | | |
| Approximate | 3% | 2% | 1% | | | |
| entrapped air | | | | | | |
| content | | | | | | |

Table:4

| | Bulk Volume of rodded CA per unit volume of | | | | |
|------------|---|------|------|------|--|
| | concrete of fineness modulus of sand of | | | | |
| Max size | Fineness modulus | | | | |
| of | 2.4 | 2.6 | 2.8 | 3.0 | |
| aggregate↓ | | | | | |
| | | | | | |
| 10 | 0.46 | 0.44 | 0.42 | 0.40 | |
| 20 | 0.65 | 0.63 | 0.61 | 0.59 | |
| 40 | 0.76 | 0.74 | 0.72 | 0.70 | |

14